

FD6194E

FD6194E FOUR-HEAD DYE SUBLIMATION PRINTER

INDUSTRIAL GRADE SPEED

180m²/h



FUNCTIONS AND FEATURES

EPSON 13200-A1 PRINTHEAD

EPSON 13200-A1 printhead has 3200 nozzles, variable drop ink technology, improves printing resolution, improves color restoration degree, up to four levels of gray print can be supported.



HIGH-END IMPORTED PARTS

German imported IGUS drag-chain and Japanese NSK bearings to ensure the high-efficiency and high-quality pictures output



LIFTABLE HEAD CAPPING STATION

Equipped with advanced intelligent printhead cleaning and moisturizing device, providing safe and convenient printhead cleaning and maintenance functions, more convenient operation and maintenance.



BULK TANK INK SUPPLY SYSTEM

Four units of 3L super large capacity ink tanks provide ink independently and continuously, which guarantees the long-term continuity of ink output.



IMPORTED THK MUTE GUIDE RAIL

Using Japanese THK mute linear guide rail, the movement is more stable and the life is longer.



ANTI COLLISION SYSTEM IN CARRIAGE

The position of the printhead can be adjusted according to different printing medias and anti-collision devices at both ends









LONGER LIFE

AUTO CLEANING

HIGH PERFORMANCE



HIGH STABILITY



HIGH EFFICIENCY



HIGH PRECISION



CMYK

(I3200-A1

PRINTHEAD TYPE

PRINT WIDTH COLOR

1900mm

TECHNICAL PARAMETERS

Machine Size

| TECHNICAL TAKAMETERS | |
|--|---|
| | |
| Model | FD6194E |
| Printhead | Type: EPSON I3200-A1 Printhead Printhead Quantity: 4, Nozzle Quantity: 3200 |
| Print Speed (Tested on linear printing without feather function) | 360*1200dpi 2PASS:180ൻ/h 360*1800dpi 3PASS:120ൻ/h 360*2400&720*1200dpi 4PASS:90ൻ/h |
| Ink Type | Type: Sublimation Ink, Color: CMYK |
| Print Width | 1900mm |
| Print Media | Transfer Paper |
| Media Transmit | Pinch Roller Mode |
| Dryer | Extra Intelligent Dryer Device |
| Moisture Mode | Full Seal Auto Moisture and Cleaning |
| Rip Software | Maintop, FlexiPRINT, ONYX, Neostampa and etc. Maintop7.0(Standard Equipped) |
| Image Format | JPG, TIF, PDF, etc. |
| Computer Configuration | Computer System: Win7 64Bits Win10 64Bits, Hard Disk: 500G or more RAM: 8G, GPU: ATI Mobility Memory 4G, CPU: Intel i7 Processor Transmission Interface: Giga-bit Ethernet Port |
| Standard Configuration | Intelligent Drying System Liquid Level Alarm System Waste Ink Alarm System |
| Working Environment | Temp.: 18°C-30°C, Humidity: 35%-65% |
| Power Supply | Input Voltage: 210-230VAC Machine Printing Power: 9KW Dryer: Max 7.2KW |
| Machine Size | Dimension: 3284*1050*1720mm |

Packing: 3458*1150*1780mm

*The technical indicators and content of the machines are subject to the actual sales of the machine. The technical parameters and content of this brochure will be changed without further notice. The right of interpretation belongs to the manufacturer.

15