

SF60-4 UV DTF PRINTER

LOGO Customization | Gift Stationery | Decoration | Signage | Packaging and Printing



FUNCTION AND CHARACTERISTIC »

- The silent linear guide rail design ensures that the carriage can run without obstacles, is stable and noise-free, and has a longer life.
- It supports a variety of printing solutions, not only can print white ink and varnish, but also supports golden hot stamping, silver hot stamping, laser and other special processes.
- The white ink stirring circulation system makes printing smoother.
- The printhead bottom plate heating function ensures printing quality in low temperature environments.
- The standard independent LED water-cooled UV curing system, fast speed, has a longer lifetime, and is perfectly combined with high-speed printing.
- Fully automatic printing and lamination are integrated into one piece, efficient and convenient.

SF60-4 UV DTF PRINTER

TECHNICAL PARAMETERS »

Model	SF60-4
Printhead Type	Epson I3200-U1 Printhead
Printhead	Printhead Cleaning: Independent Wiper Printhead Quantity: 3 One more printhead position is reserved for customization
Print Speed <small>(Based on linear 300 without varnish)</small>	4PASS: 8m ² /h 6PASS: 6m ² /h
Ink Type	UV DTF Ink
Print Color	CYMK+W+CYMK+V
Heating Mode	Rubber Roller Heating
System Configuration	CPU: Intel Core(TM)i7-9700K RAM: Kingston 8G or above Computer System: Win7 and above Network Card: Gigabit Ethernet
Print Media	AB Film, Plasma Film
Media Transmit	Automatic Roll Rewinding and Unwinding
Working Environment	Temp.:18°C-34°C, Humidity:36%-60%
Machine Size	1745*918*1480mm
Print Width	600mm
RIP Software	Maintop, RIIN, FlexiPRINT, etc.
Image Format	JPG, TIF, PDF, etc.
Power Supply	110V/220V 50-60HZ
Machine Weight	262KG

※ The above printing speed will be slightly different due to the computer, media width, temperature and humidity, please refer to the actual speed!